



ZINSSER® COVERS UP™

Stain blocking primer and finishing coat in one

- Matt white finish, for indoor use
- Primer and finishing coat in one
- Blocks stains from water, nicotine and smoke
- Ideal for retouching a ceiling
- Quick drying and low odour

ZINSSER® COVERS UP™

DESCRIPTION

COVERS UP™ is an acrylic, solvent-based stain blocking primer and ceiling paint in one. This low odour and quick drying primer ensures a matt white finish that matches the colour of most ceiling tiles and white ceiling paints. The vertical aerosol is easy to use. Ideal for retouching a ceiling. For indoor use.

RECOMMENDED USE

For indoor use. Apply as a primer / finish to interior acoustic ceiling tiles or painted ceilings, light fixtures, HVAC ductwork and vents, overhead pipes and conduit, or anywhere an overhead high hiding stain sealing primer or spot finish is needed. New, primed or previously painted ceiling tiles, drywall, cured plaster, cement, stucco, wood (pine, fir, birch, oak and plywood), aluminum, iron, steel and galvanized metal, PVC, glossy laminates and other interior surfaces.

DRY TIMES BY 20° C/RH 50%

Touch dry: 30 minutes (@ 20°C)
Dry to recoat: 2 hours

THEORETICAL CONSUMPTION

1.5 m²/aerosol

PRACTICAL CONSUMPTION

Practical coverage depends on many factors such as porosity and roughness of the substrate, type of application and material losses during application

SURFACE PREPARATION

Surfaces should be clean, dry, sound and free of dust, dirt, excessive chalky material, grime, grease, oil, wax, mildew, wallpaper adhesive or any contamination that may interfere with adhesion. If unsure, always wash surface with a household ammonia and water solution, appropriate cleaning solution, or solvent (Do not use tri sodium phosphate based cleaners). Remove any unsoundly adhered coatings. Sand any remaining paint film edges smooth with the surface. Attempt to remove existing stains by washing, sanding, scraping, etc.

DIRECTIONS FOR USE

Use at room temperature in a well-ventilated area - avoid high humidity. Shake can until ball inside rattles, then continue shaking for one minute. Repeat shaking periodically during use. Test spray pattern on scrap surface before using. Spray 25-30 cm from surface. Apply with short 'dusting' strokes. When finished, clean valve by holding can upside down and spraying until clear gas comes out. To clear clogged spray tip, remove from can and clean with pin.

APPLICATION CONDITIONS

Use at a temperature of 4 - 32°C at a humidity <85%.

CLEANING OF EQUIPMENT / SPILLS

Clean spills and drips with a rag dampened in mineral spirits.

REMARKS

COVERS UP™ is not intended for application to floors, decks, roof surfaces or any surface subject to immersion or prolonged contact with water.

SAFETY DATA

VOC category: /
Remarks regarding safety: Consult Safety Data Sheet and Safety Information printed on the aerosol.

SHELF LIFE

Minimum of 3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5 and 25°C.

Date issued: 21/05/2024

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu